Water Soaker

A new product from Hytek (GB) Ltd
Made with a super-absorbent polymer
With mesh filter containment

Product Code WS2
5.6cm x 30cm
Absorbs 489ml

Condensation occurs in most fuel tanks and can cause corrosion or poor engine starting. The Water Soaker from Hytek (GB) Ltd has been developed to remove this water, and to prevent accumulation of further water build up.

Instructions for use:

1. Select the correct size Water Soaker for your application (3 sizes available), deploy or retrieve the Water Soaker

2. Ensure there are no sources of ignition (e.g cigarettes and or other burning materials) near to the fuel tank before opening

3. Lower the Water Soaker into the fuel tank using the attached cord until the bottom of the tank is reached (the cord will go slack) – as water is more dense than fuel this is where the water will have settled – allow the Water Soaker to lie flat on the bottom of the tank

4. Ensure that the end of the cord is available to retrieve the Water Soaker when it is full (we recommend that you attach it to the underside of the fuel cap)

5. Check your Water Soaker monthly and replace every 3 months (when the Water Soaker has absorbed fully you will find that the nylon bladder has fully expanded into the mesh filter containment tube)

6. Ensure that the Water Soaker does not obstruct any sender units in the tank or the fuel outlet (very important in moving vehicles)

7. Dispose of the Water Soaker in accordance with local regulations